## NSN 5935-01-509-0695

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-509-0695

**Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 6.500 inches **Overall Diameter:** 1.312 inches **Environmental Protection:** Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant **Cable Entrance Diameter:** Between 0.281 inches and 0.438 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Andu b01 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 and 119.0 and 146.0 and 176.0 and 208.0 Shell Type: Split **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 20 and 10 **Thread Size:** 0.875 inches and 0.875 inches **Terminal Location:** Back single mating end single contact grouping

Shell Material: Aluminum

**Terminal Type:** 

Crimp single mating end single contact grouping

## **NSN 5935-01-509-0695**Electrical Plug Connector - Page 2 of 2



Cadmium Included Contact Quantity:  12 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color: Dlive drab	
12 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color:	
Included Contact Type:  Round pin single mating end single contact grouping  Special Features:  Contacts per mil-c-39029/83-508  Color:	
Round pin single mating end single contact grouping  Special Features:  Contacts per mil-c-39029/83-508  Color:	
Special Features: Contacts per mil-c-39029/83-508 Color:	
Contacts per mil-c-39029/83-508	
Color:	
Olive drah	
Onve diab	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	
Test Data Document:	
31349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific	cification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on ce	tain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef and double stub	
Specification Data:	
31349-mil-c-28840/26 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
4039b0	