NSN 5935-01-509-0705

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-509-0705

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
6.500 inches
Overall Diameter:
1.125 inches
Environmental Protection:
Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant
Cable Entrance Diameter:
Between 0.281 inches and 0.438 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
15-21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Insert Position In Deg:
0.0 and 135.0 and 170.0 and 200.0 and 310.0
Shell Type:
Split
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
20 and 10
Thread Size:
1.000 inches and 1.062 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:

Aluminum

Shell Material:

Crimp single mating end single contact grouping

NSN 5935-01-509-0705Electrical Plug Connector - Page 2 of 2



Cadmium Included Contact Quantity: 21 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color: Olive drab	
21 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color: Olive drab	
Included Contact Type: Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color: Olive drab	
Round pin single mating end single contact grouping Special Features: Contacts per mil-c-39029/83-508 Color: Olive drab	
Special Features: Contacts per mil-c-39029/83-508 Color: Olive drab	
Contacts per mil-c-39029/83-508 Color: Olive drab	
Color: Olive drab	
Olive drab	
Precious Material And Location:	
Contact surfaces gold	
Precious Material:	
Gold	
Test Data Document:	
31349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in spe	cification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cer	tain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef and double stub	
Specification Data:	
31349-mil-c-28840/26 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
4039b0	