## NSN 5935-01-510-6134

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-510-6134 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.625 inches **Overall Height:** Between 1.698 inches and 1.738 inches **Overall Width:** Between 1.698 inches and 1.738 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.281 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: **Distance From Mounting Shoulder To Front Face:** Between 0.878 inches and 0.898 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 23-64 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 116.0 and 160.0 and 191.0 and 311.0 Shell Type: Split **Connector Locking Method:** Externally threaded shell **End Application:** Los angeles class ssn (668) Thready Qty Per Inch (tpi): 10 **Thread Size:** 

1.500 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-01-510-6134

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
64 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/84-509
Color:
Olive drab
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Double stub
Specification Data:
81349-mil-c-28840/12 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0