Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-511-7657

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Unable To Decode:
Unable to decode and unable to decode and unable to decode and unable to decode
Overall Length:
1.405 inches
Overall Diameter:
Between 1.172 inches and 1.203 inches
Environmental Protection:
Corrosion resistant and fungus resistant and solvent resistant and vibration resistant and weather resistant
Distance From Mounting Shoulder To Front Face:
Between 0.658 inches and 0.707 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.187 inches
Threaded Device Type:
Back shell and hub
Mating End Quantity:
1
Contact Position Arrangement Style:
6-oct single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
24 and 24
Thread Size:
0.625 inches and 0.687 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Contacts per mil-c-39029/5-115

Color:

Black

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

96906-ms3474 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.