## NSN 5935-01-511-8049



Electrical Receptacle Connector Body - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-511-8049 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 33.6 millimeters **Overall Height:** 33.0 millimeters **Overall Width:** 33.0 millimeters **Environmental Protection:** Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather Center To Center Distance Between Mounting Facilities Parallel To Height: Between 24.6 millimeters and 26.9 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 24.6 millimeters and 26.9 millimeters **Distance From Mounting Shoulder To Front Face:** 20.8 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 17-6 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 50.0 and 160.0 and 190.0 and 225.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 175.0 degrees celsius

**Thread Size:** 

25.0 millimeters and 1.187 inches

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

## NSN 5935-01-511-8049

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.

Electrical Receptacle Connector Body - Page 2 of 2



reflect specification type data in specification

reflecting general type data on certain

Thread Tolerance Class:
6g external
Special Features:
Items furnished as accessories -protective cover
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m and special acme
Specification Data:
81349-mil-dtl-38999/20 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: