

View Online at <https://aerobasegroup.com/nsn/5935-01-512-1136>

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

43.1 millimeters

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Vibration proof and weatherproof

**Cable Entrance Diameter:**

15.8 millimeters

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-14 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Connector End:**

61.0 millimeters

**Distance From Centerline To Cable End:**

53.0 millimeters

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Included Contact Quantity:**

19 single mating end single contact grouping

**Special Features:**

Environmental

**Precious Material And Location:**

Contact surfaces silver

**Relationship To Similar Equipment (non-core):**

Interchangeable w/ but not intermatable w/ mil-c-5015 connectors - same shell dimensions and contact layouts but ca series has bayonet coupling

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0