Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-512-1619

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Unable To Decode:
Unable to decode and unable to decode
Overall Length:
1.223 inches
Overall Height:
1.219 inches
Overall Width:
1.219 inches
Unthreaded Mounting Hole Diameter:
0.128 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
0.632 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
15-15 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
34.0 and 105.0 and 132.0 and 220.0 and 265.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Operating Tempurature Rating:
Between -65.0 degrees celsius and 175.0 degrees celsius
Thread Size:
0.812 inches



# Terminal Location:

Back single mating end all contact groupings

# **Terminal Type:**

Crimp single mating end all contact groupings

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Included Contact Quantity:

14 single mating end 2nd contact grouping

# Included Contact Type:

Round socket single mating end all contact groupings

# **Special Features:**

Contacts per mil-c-39029/56-351 and 352

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unef

# Specification Data: 96906-ms27466 government standard Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-dtl-38999 spec.