Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-512-1633

View Online at https://aerobasegroup.com/nsn/5935-01-512-1633
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Unable To Decode:
Unable to decode and unable to decode
Overall Length:
1.223 inches
Overall Height:
1.562 inches
Overall Width:
1.562 inches
Unthreaded Mounting Hole Diameter:
0.128 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
0.602 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
21-16 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
105.0 and 132.0 and 220.0 and 265.0 and 342.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Operating Tempurature Rating:
Between -65.0 degrees celsius and 175.0 degrees celsius
Thread Size:
1.187 inches



## **Terminal Location:**

Back single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Cadmium

## Included Contact Quantity:

16 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

## **Special Features:**

Contacts per mil-c-39029/56-352

**Precious Material And Location:** 

Contact surfaces gold

## **Precious Material:**

Gold

## **Test Data Document:**

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

# Specification Data: 96906-ms27466 government standard Shelf Life:

N/a

Unit Of Measure:

```
---
```

## **Demilitarization:**

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-dtl-38999 spec.