NSN 5935-01-512-2674

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-512-2674 **Body Style:** Straight shape, internal coupling Overall Length: 1.500 inches **Overall Diameter:** 0.750 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 40393 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 60.0 Shell Type: Potting **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Potting type **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-512-2674

Electrical Plug Connector - Page 2 of 2



| P | racions | Matarial | And | Location: |
|---|---------|----------|------|-----------|
| _ | recious | wateriai | Allu | LOCALION. |

Contact surface gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0