## NSN 5935-01-515-3563

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-515-3563

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Angle shape w/cable clamp
Overall Diameter:
1.825 inches
Body Angle In Deg:
135.0
Environmental Protection:
Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant
Cable Entrance Diameter:
Between 0.625 inches and 0.938 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
G01 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key or multiple key
Insert Position In Deg:
0.0 and 135.0 and 170.0 and 200.0 and 310.0
Shell Type:
Solid
Connector Cable Strain Relief Method:
Cable clamp
End Application:
Misc.Parts, virginia class submarine, ssn774
Distance From Centerline To Connector End:
8.371 inches
Distance From Centerline To Cable End:
5.932 inches
Thready Qty Per Inch (tpi):
18 and 10
Thread Size:
1.562 inches and 1.562 inches

Back single mating end single contact grouping

**Terminal Location:** 

## **NSN 5935-01-515-3563**Electrical Plug Connector - Page 2 of 2



Ferminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
22 single mating end single contact grouping
ncluded Contact Type:
Round pin single mating end single contact grouping
Special Features:
Contacts per mil-c-39029/83-450
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
31349-mil-c-28840/29 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jnef and double stub
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A039b0