

View Online at <https://aerobasegroup.com/nsn/5935-01-515-9390>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling w/backshell

**Unable To Decode:**

Unable to decode and unable to decode

**Overall Length:**

6.625 inches

**Overall Height:**

Between 1.003 inches and 1.043 inches

**Overall Width:**

Between 1.003 inches and 1.043 inches

**Environmental Protection:**

Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.878 inches and 0.898 inches

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

40489 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 124.0 and 152.0 and 219.0 and 265.0

**Shell Type:**

Split

**Connector Locking Method:**

Externally threaded shell

**End Application:**

Virginia class submarine ssn-774

**Thready Qty Per Inch (tpi):**

20 and 10

**Thread Size:**

0.750 inches and 0.750 inches

**Terminal Location:**

Back single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Contacts per mil-c-39029/84-452

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un and double stub

**Specification Data:**

81349-mil-c-28840/20 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0