

View Online at <https://aerobasegroup.com/nsn/5935-01-517-5444>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.662 inches

**Overall Height:**

Between 1.250 inches and 1.312 inches

**Overall Width:**

Between 1.250 inches and 1.312 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.953 inches and 0.985 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.953 inches and 0.985 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.562 inches and 0.593 inches

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

16s-1 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

80.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

1.000 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium and chromate and nickel

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3412 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-dtl-5015 spec.