## NSN 5935-01-517-8156

**Thread Direction:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-517-8156

Till Cad Direction.
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
32.5 millimeters
Overall Diameter:
Between 37.8 millimeters and 38.4 millimeters
Distance From Mounting Shoulder To Front Face:
22.6 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
13-8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0 and 95.0 and 141.0 and 208.0 and 236.0
Shell Type:
Solid
Thread Size:
25.0 millimeters
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum
Thread Tolerance Class:
6g external
Included Contact Quantity:
8 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping

**Supplementary Features:** Mounting method - jam mut

## NSN 5935-01-517-8156

Electrical Receptacle Connector - Page 2 of 2



## **Test Data Document:**

81349-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m
Specification Data:
81349-38999/24 government specification
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.

Demilitarization: