Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-518-3267

| Body Style:   |
|---|
| Rectangular shape w/tabs                                  |
| Overall Length:   |
| 23.8 millimeters  |
| Overall Height:   |
| Between 12.15 millimeters and 12.45 millimeters           |
| Overall Width:  |
| Between 18.65 millimeters and 18.95 millimeters           |
| Body Length:  |
| Between 19.85 millimeters and 23.15 millimeters           |
| Mating End Quantity:                                      |
| 1   |
| Contact Position Arrangement Style:                       |
| 5025-02 single mating end                                 |
| Contact Removability:                                     |
| Removable single mating end all contact groupings         |
| Contact Maximum Current Rating In Amps:                   |
| 30.0 single mating end all contact groupings              |
| Shell Type:   |
| Solid   |
| Connector Locking Method:                                 |
| Push-pull and clip  |
| Connector Cable Strain Relief Method:                     |
| Wedge-lock  |
| End Application:  |
| 2320-01-432-4847; wsd: truck, m-915 series, m-916a1 (let) |
| Operating Tempurature Rating:                             |
| Between -40.0 degrees celsius and 125.0 degrees celsius   |
| Terminal Location:  |
| Back single mating end all contact groupings              |
| Contact Material:   |
| Copper alloy single mating end all contact groupings      |
| Contact Surface Treatment:                                |
| Tin single mating end all contact groupings               |
| Terminal Type:  |
| Tab, solder lug single mating end all contact groupings   |
| Shell Material:   |
| Plastic polyamide   |
| Included Contact Quantity:                                |
| 2 single mating end all contact groupings                 |
| Color:  |
| Gray  |
| /   |

## NSN 5935-01-518-3267

Electrical Plug Connector - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

