Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-520-4426

## Thread Class:

2b

Thread Direction:

Right-hand and right-hand

# Body Style:

Straight shape, internal coupling

#### Overall Length:

31.0 millimeters

#### **Overall Diameter:**

31.3 millimeters

#### **Environmental Protection:**

Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather resistant

# Threaded Device Type:

Back shell and coupling facility

# Mating End Quantity:

1

**Contact Position Arrangement Style:** 

24-24 single mating end

## Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0 and 135.0 and 170.0 and 200.0 and 310.0

## Shell Type:

Solid

## **Connector Locking Method:**

Internally threaded coupling ring

#### Thread Size:

1.0 millimeters and 1.625 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Resin synthetic

#### Shell Surface Treatment:

Cadmium

## **Thread Tolerance Class:**

6g external

#### **Included Contact Quantity:**

12 single mating end 2nd contact grouping

# NSN 5935-01-520-4426

Electrical Plug Connector - Page 2 of 2



#### Included Contact Type:

Round socket single mating end all contact groupings

#### **Special Features:**

Contacts per m39029/56-363 and m39029/56-352

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator: Iso m and special acme

Specification Data:

81349 - mil-dtl-38999/26 government specification

Shelf Life:

N/a

---

Unit Of Measure:

**Demilitarization:** No

Fiig:

i iig.

A039b0