

View Online at <https://aerobasegroup.com/nsn/5935-01-520-5324>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Unable To Decode:

Unable to decode and unable to decode and unable to decode and unable to decode

Overall Length:

33.6 millimeters

Overall Height:

46.0 millimeters

Overall Width:

33.3 millimeters

Environmental Protection:

Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 34.9 millimeters and 38.1 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 34.9 millimeters and 38.1 millimeters

Distance From Mounting Shoulder To Front Face:

18.7 millimeters

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

25-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 80.0 and 180.0 and 215.0 and 298.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded shell

Thread Size:

1.0 millimeters and 1.625 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Resin synthetic

Shell Surface Treatment:

Cadmium

Thread Tolerance Class:

6g external

Included Contact Quantity:

128 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Contacts per mil-c-39029/58-360

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349 - mil-dtl-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0