## NSN 5935-01-520-6120

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-520-6120

**Body Style:** Straight shape, external coupling **Overall Length:** 1.215 inches **Overall Height:** 1.360 inches **Overall Width:** 1.360 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.031 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.031 inches **Distance From Mounting Shoulder To Front Face:** 0.493 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-19 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet shell **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 19 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-01-520-6120

Mil-std (military Standard):

Mil-c-26482 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906 - ms3472 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0