## NSN 5935-01-522-1699

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-522-1699

**Body Style:** Straight shape, external coupling **Overall Length:** 1.039 inches **Overall Height:** 1.031 inches **Overall Width:** 1.031 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** 0.820 inches **Mating End Quantity: Contact Position Arrangement Style:** 13089 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 28.0 and 105.0 and 132.0 and 220.0 and 265.0 Shell Type: Solid **Connector Locking Method:** Bayonet shell **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and nickel **Included Contact Quantity:** 13 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

## NSN 5935-01-522-1699

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906 - ms27505 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-dtl-38999 spec.

A039b0