NSN 5935-01-522-1716

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-522-1716

204, 0.5.0.
Straight shape, external coupling
Overall Length:
1.039 inches
Overall Height:
1.031 inches
Overall Width:
1.031 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Distance From Mounting Shoulder To Front Face:
0.820 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
13089 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
105.0 and 132.0 and 220.0 and 265.0 and 332.0
Shell Type:
Solid
Connector Locking Method:
Bayonet shell
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and nickel
Included Contact Quantity:
13 single mating end single contact grouping
Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-01-522-1716

Mil-std (military Standard):

Mil-dtl-38999 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906 - ms27505 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0