NSN 5935-01-522-1763

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-522-1763

Body Style: Straight shape, external coupling **Overall Length:** 1.039 inches **Overall Height:** 1.219 inches **Overall Width:** 1.219 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.968 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.968 inches **Distance From Mounting Shoulder To Front Face:** 0.825 inches **Mating End Quantity: Contact Position Arrangement Style:** 15-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 105.0 and 132.0 and 220.0 and 265.0 and 326.0 Shell Type: Solid **Connector Locking Method:** Bayonet shell **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel and cadmium **Included Contact Quantity:** 37 single mating end single contact grouping **Included Contact Type:**

moraded Contact Type

Round socket single mating end single contact grouping

NSN 5935-01-522-1763

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
Mil-dtl-38999 standard (includes industry or association standards, individual manufactureer standards, etc.)
Specification Data:
96906 - ms27505 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-dtl-38999 snec