## NSN 5935-01-522-2342

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-522-2342 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.792 inches **Environmental Protection:** Fire resistant and humidity resistant and moisture resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 28-12 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.4375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Glass fiber single mating end **Terminal Type:** Crimp single mating end single contact grouping

Shell Material:

Steel

## NSN 5935-01-522-2342

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
22 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Supplementary Features:
Mounting method - clamp
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0