NSN 5935-01-522-3095

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-522-3095 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.290 inches **Overall Height:** 1.823 inches **Overall Width:** 1.823 inches **Unable To Decode:** Unable to decode and unable to decode **Unable To Decode:** Unable to decode and unable to decode **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 1.375 inches and 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.375 inches and 1.500 inches **Distance From Mounting Shoulder To Front Face:** Between 0.785 inches and 0.790 inches **Mating End Quantity: Contact Position Arrangement Style:** 25-11 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 135.0 and 170.0 and 200.0 and 310.0 **Connector Locking Method:** Externally threaded shell **Features Provided:** Color band engagement indicator **Thread Size:** 1.625 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

Shell Material: Aluminum

NSN 5935-01-522-3095

Electrical Receptacle Connector - Page 2 of 2



Ch all	C	:	T	L	4.
Shell	Suri	ace	ı rea	ımen	τ:

Cadmium and chromate

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Is 500 hour salt spray resistant.

Supplementary Features:

Mounting method - slot

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0