NSN 5935-01-524-7515

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-524-7515 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 2.870 inches **Overall Diameter:** 1.010 inches **Threaded Device Type:** Mounting stud **Contact Maximum Frequency Rating:** 10.9 gigahertz single mating end single contact grouping Shell Type: Solid Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Operating Tempurature Rating:** Between -40.0 degrees celsius and 150.0 degrees celsius Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Shell Material:** Copper alloy **Shell Surface Treatment:** Silver **Shell Surface Treatment Specification:** Qq-s-365d, type iii, grade a, 120-160 vpn federal specification single treatment response **Shell Material Specification:** Astm b16 assn standard single material response **Special Features:** Inner attachment method spring fingers; outer attachment method self flare **Precious Material And Location:** Body, flar ring, clamping nut, pipe plug silver and inner connector gold **Precious Material:** Silver and gold **Supplementary Features:** Mounting method - threaded body **Thread Series Designator:** Unef Shelf Life:

N/a

NSN 5935-01-524-7515

Electrical Receptacle Connector - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A039b0