

View Online at <https://aerobasegroup.com/nsn/5935-01-525-2753>

**Thread Class:**

2a and 2a

**Thread Direction:**

Left-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 1.643 inches and 1.684 inches

**Overall Height:**

Between 1.730 inches and 1.771 inches

**Overall Width:**

Between 1.730 inches and 1.771 inches

**Environmental Protection:**

Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.172 inches and 0.182 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.375 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.375 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.797 inches and 0.807 inches

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-22 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**End Application:**

Nsn 4940-01-471-6396; electronic shop, transportable; w/s: missile, patrol

**Thready Qty Per Inch (tpi):**

18 and 10

**Thread Size:**

1.375 inches and 1.500 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Connector, receptacle, electrical, wall-mounted

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and double stub

**Specification Data:**

96906-ms17343 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-22992 spec.