NSN 5935-01-526-6483



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-526-6483 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.937 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.750 inches and 0.781 inches **Mating End Quantity: Contact Position Arrangement Style:** 22-2 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 70.0 **End Application:** Pierside junction box assembly **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-526-6483

A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906 - ms3452 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: