NSN 5935-01-526-6816

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-526-6816 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Unable To Decode:** Unable to decode and unable to decode and unable to decode **Overall Length:** 1.700 inches **Overall Diameter:** 0.810 inches **Distance From Mounting Shoulder To Front Face:** 0.950 inches **Mating End Quantity: Contact Position Arrangement Style:** N single mating end **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Crimp type Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Beryllium single mating end single contact grouping and copper single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:**

Nickel

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-01-526-6816

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Furnished items - nut and washer
Precious Material And Location:
Contact plating gold
Precious Material:
Gold
Supplementary Features:
Mounting method - bushing
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0