

View Online at <https://aerobasegroup.com/nsn/5935-01-526-7732>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external/internal coupling

**Overall Length:**

29.3 millimeters

**Overall Diameter:**

10.8 millimeters

**Threaded Device Type:**

Coupling facility and coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

F all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

30.0 all mating ends single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

50.0 all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

1000.0 megahertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut and externally threaded shell

**End Application:**

Ael 90006000-95 (3j458) , 27tv support equipment

**Thread Size:**

0.375 inches and 0.375 inches

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Special Features:**

F female to f male voltage blocking coupler

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0