

View Online at <https://aerobasegroup.com/nsn/5935-01-526-7732>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external/internal coupling

Overall Length:

29.3 millimeters

Overall Diameter:

10.8 millimeters

Threaded Device Type:

Coupling facility and coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

F all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

30.0 all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

50.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

1000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut and externally threaded shell

End Application:

Ael 90006000-95 (3j458) , 27tv support equipment

Thread Size:

0.375 inches and 0.375 inches

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

1 all mating ends single contact grouping

Special Features:

F female to f male voltage blocking coupler

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0