## NSN 5935-01-526-9151

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-526-9151
Body Style:
Straight shape, external coupling
Unable To Decode:
Unable to decode and unable to decode and unable to decode
Overall Length:
1.662 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
Environmental Protection:
Corrosion resistant and salt spray proof and shock resistant and vibration resistant and weather resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Distance From Mounting Shoulder To Front Face:
0.843 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
24-28 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
280.0
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Included Contact Quantity:

24 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-01-526-9151

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Furnished items - spare contact and sealing plug and protective cover
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906 - ms3402 government specification

Demilitarization:

**Unit Of Measure:** 

Shelf Life:

No

N/a

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.