

View Online at <https://aerobasegroup.com/nsn/5935-01-527-9317>

Thread Class:

2a

Thread Pitch Diameters:

+0.228 to 0.231 inches

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

22.2 millimeters

Overall Diameter:

6.4 millimeters

Distance From Mounting Shoulder To Front Face:

14.6 millimeters

Mounting Facility Thickness:

1.7 millimeters

Mating End Quantity:

2

Contact Position Arrangement Style:

Rf all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Connector Locking Method:

Externally threaded shell

End Application:

Nsn: 5411-01-436-3326; shelter, non expandable, lightweight, multi purpose.

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Material:

Beryllium and copper all mating ends single contact grouping

Contact Surface Treatment:

Copper and gold all mating ends single contact grouping

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Product Name:

Jack to jack bulkhead feedthrough.

Special Features:

Panel attachment, rear mount on bulkhead.

Precious Material And Location:

Contact surfact treatment. Gold

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0