

View Online at <https://aerobasegroup.com/nsn/5935-01-528-6688>

Body Style:

Angle, shape, internal coupling

Overall Length:

0.666 inches

Environmental Protection:

Vibration resistant and shock resistant and thermal shock resistant and moisture resistant and corrosion resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Osm single mating end

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Shrinkable tubing

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end all contact groupings

Distance From Centerline To Cable End:

1.020 inches

Width Across Flats:

0.312 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Beryllium single mating end all contact groupings and copper single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic fluorocarbon single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Stainless steel

Shell Surface Treatment:

Gold and nickel

Included Contact Quantity:

1 single mating end all contact groupings

Included Contact Type:

Coaxial pin single mating end all contact groupings

Precious Material And Location:

Contact, shell, and ferrule plating. Gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0