NSN 5935-01-529-3034

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-529-3034 **Thread Class:** 2b and 2a **Thread Direction:** Right-hand **Body Style:** Angle shape, pcb type **Overall Length:** Between 4.340 inches and 4.360 inches **Overall Height:** 0.530 inches **Overall Width:** 0.250 inches **Environmental Protection:** Vibration resistant and salt spray proof and shock resistant and humidity resistant and fungus resistant **Distance Between Mounting Facility Centers:** 4.100 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Maximum Current Rating In Amps:** 5.0 single mating end all contact groupings **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew **End Application:** Aircraft, hornet f/a-18 **Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Side single mating end all contact groupings **Contact Material:**

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Terminal Type:

Printed circuit single mating end all contact groupings

NSN 5935-01-529-3034

A039b0

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
70 single mating end all contact groupings
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Jackscrew type-male and location-right handandjackscrew type-female and location-left hand
Precious Material And Location:
Contact plating gold
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: