

View Online at <https://aerobasegroup.com/nsn/5935-01-530-0331>

Body Style:

Straight shape

Overall Length:

1.350 inches

Overall Height:

1.215 inches

Overall Width:

0.250 inches

Environmental Protection:

Vibration resistant and shock resistant and humidity resistant

Distance Between Mounting Facility Centers:

1.150 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end all contact groupings

Polarization Method:

Jackscrew

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Contact Surface Treatment Specification:

Astm b 488 and sae-ams 2422 assn standard single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Mil-c-55302 military specification single material response single mating end all contact groupings

Shell Material:

Plastic polyphenylene sulfide

Shell Material Specification:

Mil-m-24519, type gst-40f military specification single material response

Included Contact Quantity:

20 single mating end all contact groupings

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Terminal surface finish gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-55302 spec.