

View Online at <https://aerobasegroup.com/nsn/5935-01-530-9356>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.240 inches

**Overall Diameter:**

1.104 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and vibration proof

**Distance From Mounting Shoulder To Front Face:**

0.781 inches

**Mounting Facility Thickness:**

0.125 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

40456 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 105.0 and 140.0 and 215.0 and 265.0

**Shell Type:**

Solid

**End Application:**

Cams video switch

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Included Contact Quantity:**

5 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-dtl-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349 - mil-dtl-83723/85 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0