NSN 5935-01-531-6536

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-531-6536

Overall Length:

1.219 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.485 inches

Overall Width:

1.219 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.485 inches

Cable Entrance Diameter:

0.812 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

6.37 single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Potting

Connector Locking Method:

Bayonet pin

End Application:

6625-01-492-9713, test program set

Operating Tempurature Rating:

-65.0 degrees celsius and 200.0 degrees celsius

Contact Material:

Stainless steel single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

Mounting method-unthreaded hole

Color:

Olive drab

Supplementary Features:

Insert material: reinforced epoxy resin

NSN 5935-01-531-6536

Electrical Receptacle Connector - Page 2 of 2



Test Data Document:

81349-dtl38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906 - 27466 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.