

View Online at <https://aerobasegroup.com/nsn/5935-01-532-1387>

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

6.313 inches

Overall Diameter:

1.469 inches

Environmental Protection:

Corrosion resistant and salt spray proof and shock resistant and vibration resistant and weather resistant

Cable Entrance Diameter:

Between 0.350 inches and 0.625 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

20-19 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

End Application:

An/spn-35c misc parts

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Contacts per mil-c-39029/45-298

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906 - ms3406 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.