NSN 5935-01-534-0972

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-534-0972 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.838 inches **Overall Height:** 0.828 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.594 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36434 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-534-0972

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.006 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27497 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli