

View Online at <https://aerobasegroup.com/nsn/5935-01-534-2053>

**Thread Direction:**

Right-hand

**Unthreaded Mounting Hole Diameter:**

0.102 inches

**Cable Entrance Diameter:**

0.050 inches

**Mating End Quantity:**

1

**Contact Maximum Dc Voltage Rating In Volts:**

18.0 single mating end single contact grouping

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-prf-39012 military specification single treatment response single mating end single contact grouping

**Shell Material:**

Steel comp 303

**Shell Material Specification:**

Astm a582 assn standard single material response

**Included Contact Quantity:**

2 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-prf-39012 spec.