## NSN 5935-01-534-5892

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-534-5892 **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Mating End Quantity: Contact Position Arrangement Style:** 20-19 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 180.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material:** 

Gold

## NSN 5935-01-534-5892

Electrical Receptacle Connector - Page 2 of 2



## **Test Data Document:**

81349-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

| 96906 - | ms3102 | government | specification |
|---------|--------|------------|---------------|
|         |        |            |               |

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-5015 spec.