

View Online at <https://aerobasegroup.com/nsn/5935-01-534-7915>

**Body Style:**

Rectangular shape

**Environmental Protection:**

Vibration resistant and shock resistant and thermal shock resistant and moisture resistant and corrosion resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Osm single mating end

**Contact Maximum Current Rating In Amps:**

3.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end all contact groupings

**Connector Locking Method:**

Jackscrew-socket

**Connector Cable Strain Relief Method:**

Shrinkable tubing

**End Application:**

Nsn 4940-01-471-6396; electronic shop, transportable; w/s: missile, patrol

**Width Across Flats:**

0.312 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and copper single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Gold and nickel

**Included Contact Quantity:**

1 single mating end all contact groupings

**Included Contact Type:**

Coaxial pin single mating end all contact groupings

**Product Name:**

Bulk kit, plug, amplimite solder cup sheilding enclosure, 15 position, size 2

**Color:**

Black

**Precious Material And Location:**

Contact, coupling nut, body, and ferrule plating. Gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0