

View Online at <https://aerobasegroup.com/nsn/5935-01-536-6538>

Body Style:

Rectangular shape

Environmental Protection:

Vibration resistant and shock resistant and thermal shock resistant and moisture resistant and corrosion resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Osm single mating end

Contact Maximum Current Rating In Amps:

3.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end all contact groupings

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Shrinkable tubing

End Application:

Nsn 4940-01-471-6396; electronic shop, transportable; w/s: missile, patrol

Width Across Flats:

1.650 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and copper single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Stainless steel

Shell Surface Treatment:

Gold and nickel

Included Contact Quantity:

1 single mating end all contact groupings

Included Contact Type:

Coaxial pin single mating end all contact groupings

Product Name:

Bulk kit, plug, amplimite solder cup sheilding enclosure, 15 position, size 2

Color:

Black

Precious Material And Location:

Contact, coupling nut, body, and ferrule plating. Gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0