Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-536-7233

## **Body Style:** Flush flange mounting **Overall Length:** 2.220 inches **Bushing Diameter:** 2.060 inches **Mounting Hole Circle Radius:** 2.040 inches **Overall Diameter:** 2.880 inches **Unthreaded Mounting Hole Diameter:** 0.187 inches **Distance From Mounting Shoulder To Rear Face:** 2.090 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 3 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 20.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 125.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 125.0 single mating end all contact groupings **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Contact twistlock **End Application:** Nsn 4510-01-477-7763; containerized, shower **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Steel single mating end all contact groupings and nickel single mating end all contact groupings **Insert Material:** Plastic polyamide single mating end **Terminal Type:**

Screw single mating end all contact groupings

# NSN 5935-01-536-7233

Electrical Receptacle Connector - Page 2 of 2



#### Shell Material:

Glass fiber

Included Contact Quantity:

2 single mating end all contact groupings

Included Contact Type:

Curved pin w/inside lip single mating end all contact groupings

#### **Special Features:**

Nema no. L5-20r, voltage color code - yellow

#### Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A039b0