NSN 5935-01-539-1107

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-539-1107 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.654 inches **Environmental Protection:** Waterproof and explosion proof and corrosion resistant and vibration resistant and shock resistant **Distance From Mounting Shoulder To Front Face:** Between 0.766 inches and 0.782 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 24-58 single mating end **Polarization Method:** Key or multiple key **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Included Contact Quantity:** 13 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact plating gold and contact plating silver **Precious Material:** Gold and silver **Thread Series Designator:** Double stub Shelf Life:

N/a

NSN 5935-01-539-1107

Electrical Receptacle Connector - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A039b0