NSN 5935-01-540-5557

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-540-5557

Body Style: Straight shape, internal coupling w/strain relief **Body Length:** 8.312 inches **Overall Diameter:** 2.343 inches **Environmental Protection:** Corrosion resistant and fungus resistant and salt water resistant and shock resistant and vibration resistant and weather resistant **Cable Entrance Diameter:** Between 1.000 inches and 1.380 inches **Mating End Quantity: Contact Position Arrangement Style:** H01 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key or multiple key **Insert Position In Deg:** 0.0 and 80.0 and 142.0 and 196.0 and 293.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **End Application:** Data distribution subsystem **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 121 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping

Contacts per mil-c-39029/84-452

Special Features:

NSN 5935-01-540-5557

Electrical Plug Connector - Page 2 of 2



Precious	Material	And	Location:	

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349 - mil-c-28840/26 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0