

View Online at <https://aerobasegroup.com/nsn/5935-01-542-3222>

**Body Style:**

Angle shape

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Thermal shock resistant and corrosion resistant and shock resistant and vibration resistant

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Smb all mating ends

**Shell Type:**

Solid

**End Application:**

Mk119 mod0, gun computer system cabinet

**Distance From Centerline To Connector End:**

0.440 inches

**Distance From Centerline To Cable End:**

0.380 inches

**Width Across Flats:**

0.250 inches

**Features Provided:**

Captive contact

**Terminal Location:**

Side 2nd mating end single contact grouping

**Terminal Type:**

Quick disconnect, male 1st mating end single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 all mating ends all contact groupings

**Included Contact Type:**

Coaxial pin 1st mating end single contact grouping

**Product Name:**

50 ohm cmb right angle crimp type plug - captivated contact

**Special Features:**

All parts except polytetrafluoroethylene insulator are plated with gold over nickel over copper; body and end cap are brass; interface and contact are beryllium copper; crimp sleeve is copper

**Precious Material And Location:**

Plating on body, interface, contact, crimp sleeve and end cap gold

**Precious Material:**

Gold

**Supplementary Features:**

Brass, right angle crimp type plug with captivated contact; 4 ghz, 50 ohm, male, cable type: rg-178; u, 196

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0