

View Online at <https://aerobasegroup.com/nsn/5935-01-542-3222>

Body Style:

Angle shape

Body Angle In Deg:

90.0

Environmental Protection:

Thermal shock resistant and corrosion resistant and shock resistant and vibration resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

Smb all mating ends

Shell Type:

Solid

End Application:

Mk119 mod0, gun computer system cabinet

Distance From Centerline To Connector End:

0.440 inches

Distance From Centerline To Cable End:

0.380 inches

Width Across Flats:

0.250 inches

Features Provided:

Captive contact

Terminal Location:

Side 2nd mating end single contact grouping

Terminal Type:

Quick disconnect, male 1st mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 all mating ends all contact groupings

Included Contact Type:

Coaxial pin 1st mating end single contact grouping

Product Name:

50 ohm cmb right angle crimp type plug - captivated contact

Special Features:

All parts except polytetrafluoroethylene insulator are plated with gold over nickel over copper; body and end cap are brass; interface and contact are beryllium copper; crimp sleeve is copper

Precious Material And Location:

Plating on body, interface, contact, crimp sleeve and end cap gold

Precious Material:

Gold

Supplementary Features:

Brass, right angle crimp type plug with captivated contact; 4 ghz, 50 ohm, male, cable type: rg-178; u, 196

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0