NSN 5935-01-545-4949

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-545-4949 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 27.0 millimeters **Overall Diameter:** 12.5 millimeters **Distance From Mounting Shoulder To Front Face:** 10.8 millimeters **Mounting Facility Thickness:** Between 1.5 millimeters and 2.9 millimeters **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **End Application:** General purpose electronic test equipment gpete **Operating Tempurature Rating:** Between -65.0 degrees celsius and 165.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:**

Nickel

NSN 5935-01-545-4949

Electrical Receptacle Connector - Page 2 of 2



ncluded	Contact	Quantity:
---------	---------	-----------

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact plating gold

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0