Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-545-4949

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
27.0 millimeters
Overall Diameter:
12.5 millimeters
Distance From Mounting Shoulder To Front Face:
10.8 millimeters
Mounting Facility Thickness:
Between 1.5 millimeters and 2.9 millimeters
Mating End Quantity:
Contact Position Arrangement Style:
Bnc single mating end
Connector Locking Method:
Bayonet pin
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
End Application:
General purpose electronic test equipment gpete
Operating Tempurature Rating:
Between -65.0 degrees celsius and 165.0 degrees celsius
Thready Qty Per Inch (tpi):
32
Thread Size:
0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel

## NSN 5935-01-545-4949 Electrical Receptacle Connector - Page 2 of

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat Included Contact Type: Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact plating gold **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0