

View Online at <https://aerobasegroup.com/nsn/5935-01-545-8867>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.170 inches

Cable Entrance Diameter:

0.250 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Maximum Dc Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

3.0 gigahertz all mating ends single contact grouping

Connector Locking Method:

Contact twistlock

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Contact Material:

Beryllium and copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver and gold single mating end single contact grouping

Product Name:

Bma bulkhead jack

Special Features:

Dielectric is polytetrafluoroethylene ptfе; gaskets are nitrile rubber; backnut silver plated copper

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0