NSN 5935-01-549-1883

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-549-1883 **Body Style:** Straight shape, external coupling **Overall Length:** 33.6 millimeters **Overall Height:** 39.7 millimeters **Overall Width:** 39.7 millimeters **Environmental Protection:** Corrosion resistant and fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant and weather resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 29.3 millimeters and 31.7 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 29.3 millimeters and 31.7 millimeters **Distance From Mounting Shoulder To Front Face:** 20.0 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 21-35 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 116.0 and 160.0 and 191.0 and 311.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Terminal Location:** Back single mating end single contact grouping **Terminal Type:**

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

79 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-01-549-1883

Electrical Receptacle Connector - Page 2 of 2



Special	Features:
---------	-----------

Contacts per mil-c-39029/56-348; 1500-cycle socket contacts

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349 - mil-dtl-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0